

SKALFLEX BETO-BINDER

PRIMER AND DUSTBINDER FOR
MINERAL SURFACES

PAREX
Building expertise, together



DESCRIPTION

SKALFLEX BETO-BINDER is an acrylic based primer and dustbinder for mineral surfaces.

SKALFLEX BETO-BINDER improves bonding and curing – even when thin layers of paint are applied.

SKALFLEX BETO-BINDER is milky white when wet, transparent when dry.

SKALFLEX BETO-BINDER can be used as a dilution for cement based masonry paints like SKALCEM 100.

SUBSTRATES

SUITABLE SUBSTRATES

- For un-painted external and internal substrates e.g. smooth, low porosity substrates such as cast concrete, concrete panels or engineering bricks or high absorption substrates such as lightweight aircrete blockwork, common bricks and well adhered, render surfaces.

PREPARATION

The surface must be solid, clean and free of paint, lime, salt, dust and other contamination.

MIXING

Shake well before use.

Mix SKALFLEX BETO-BINDER in a clean container with clean potable, cold water in the ration 1:3 (1 part SKALFLEX BETO-BINDER to 3 parts of water).

PRECAUTIONS

- Do not dilute the product unless using as recommended in the mixing applications.
- Do not apply on wet substrates.
- Temperature range : +5°C to + 30°C.

APPLICATION

Apply SKALFLEX BETO-BINDER in an even and covering layer using brush or haired roller. Prime highly absorbent surfaces with SKALFLEX BETO-BINDER thinned with water to the ration 1:3.

The finished coating e.g. SKALCEM 100 can be applied onto the wet primer.

To improve adhesion on smooth surfaces such as concrete, replace 1 litre of the water used for mixing e.g. SKALCEM 100, with 1 litre of concentrated SKALFLEX BETO-BINDER per 10kg of SKALCEM 100 powder.

For indoor painting applications where adequate pre-wetting may be difficult to achieve, replace 1 litre of the water used for mixing e.g. SKALCEM 100, with 1 litre of concentrated SKALFLEX BETO-BINDER per 10kg of SKALCEM 100 powder.

CLEANING

After use, rinse tools with clean water.



COVERAGE

As primer 5-7 m² per litre subject to substrate

DILUTION

Water

TEMPERATURE RANGE

+5°C - + 30°C

COLOUR

Wet: White

Dry: Transparent

PACKAGING

2, 5 and 10 litres

STORAGE AND SHELF LIFE

Dry, frost free conditions

WARRANTY

Manufacturer's 10 year product indemnity including design when a Parex specification is issued. Subject to conditions.

HEALTH AND SAFETY

Wear suitable protective clothing, gloves and eye / face protection. This product contains materials which may cause an allergic reaction, is irritating to eyes and harmful if swallowed. In case of contact, seek medical advice. Keep out of the reach of children.

Read and follow the guidelines in the Health and Safety data sheet for this product.

TECHNICAL ASSISTANCE

PAREX will, on request, provide information and assistance to companies in relation to the use of a specific product.

Such assistance shall not be associated with structural and design conception, nor assume or accept liability for compliance of substrates, nor compliance to instructions provided.

Technical Information

01827 711755

Download the technical datasheet and consult the health and safety document on:

www.parex.co.uk