



## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : EHI GM

Product code : F\_EHI.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Construction, ready-to-wet mortar

Refer to the technical data sheet

Thick hydraulic render.

#### 1.3. Details of the supplier of the safety data sheet

Registered company name : PAREXGROUP S.A.

Address : 19, place de la résistance - CS 50053.92445.Issy les Moulineaux Cedex.France.

Telephone : (33)01.41.17.20.00. Fax : 01.41.17.21.30.

fds.matiere-fr@parex-group.com

www.parexlanko.com

For UK : Emergency telephone number : 01827 711755 (Mon - Fri 08:30 - 16:30).

#### 1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

### SECTION 2 : HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

#### 2.2. Label elements

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05



GHS07

Signal Word :

DANGER

Product identifiers :

EC 266-043-4

PORTLAND CEMENT CLINKER

EC 285-561-1

HYDRAULIC LIME

EC 215-137-3

CALCIUM DIHYDROXIDE

EC 270-659-9

FLUE DUST, PORTLAND CEMENT

Hazard statements :

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

H318

Causes serious eye damage.

Precautionary statements - General :

P102

Keep out of reach of children.

Precautionary statements - Prevention :

P261

Avoid breathing dust.

EHI GM - F\_EHI

P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - Response :	
P302 + P352	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or a doctor.
Precautionary statements - Disposal :	
P501	To eliminate the contents / packaging in a waste collection point. Beforehand, the product should be inerted by hardening in the water and the packagings should be completely emptied.

### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

#### Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: 2076 CAS: 14808-60-7 EC: 238-878-4 REACH: EXEMPTÉ		[1]	50 $\leq$ x % < 100
QUARTZ INDEX: 2786 CAS: 471-34-1 EC: 207-439-9 REACH: EXEMPTÉ		[1]	10 $\leq$ x % < 25
CALCIUM CARBONATE INDEX: 2999 CAS: 65997-15-1 EC: 266-043-4 REACH: EXEMPTÉ	GHS07, GHS05 Dgr Skin Irrit. 2, H315 Skin Sens. 1B, H317 Eye Dam. 1, H318 STOT SE 3, H335	[1]	10 $\leq$ x % < 25
PORTLAND CEMENT CLINKER INDEX: 2335 CAS: 1317-65-3 EC: 215-279-6 REACH: EXEMPTÉ		[1]	2.5 $\leq$ x % < 10
NATURAL CALCIUM CARBONATE INDEX: 2270 CAS: 85117-09-5 EC: 285-561-1 REACH: 01-2119475523-36-0004	GHS07, GHS05 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335		2.5 $\leq$ x % < 10
HYDRAULIC LIME INDEX: 1049 CAS: 1305-62-0 EC: 215-137-3 REACH: 01-2119475151-45	GHS07, GHS05 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335	[1]	2.5 $\leq$ x % < 10
CALCIUM DIHYDROXIDE INDEX: 2821 CAS: 68475-76-3 EC: 270-659-9 REACH: 01-2119486767-17-0003	GHS07, GHS05 Dgr Skin Irrit. 2, H315 Skin Sens. 1B, H317		0 $\leq$ x % < 2.5

FLUE DUST, PORTLAND CEMENT

Eye Dam. 1, H318  
STOT SE 3, H335

(Full text of H-phrases: see section 16)

**Information on ingredients :**

[1] Substance for which maximum workplace exposure limits are available.

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. Description of first aid measures****In the event of exposure by inhalation :**

Wash nose and throat with water (only if the victim is conscious). Remove the person outdoors to fresh air. In case of respiration trouble, consult a doctor.

**In the event of splashes or contact with eyes :**

Rinse IMMEDIATELY with a large amount of water for at least 15 minutes holding the eyelids open. Consult immediately an eye doctor.

**In the event of splashes or contact with skin :**

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

For dry powder, eliminate the dust and wash copiously with water. For wet powder, wash with a large amount of water.

**In the event of swallowing :**

For small quantities, rinse the mouth with water and seek medical advice. For large quantities, do not allow the person to drink, do not cause the person to vomit. Transfer the person to a hospital and show the product label or this material safety data sheet to the medical staff on duty.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed****Specific and immediate treatment :**

Wash copiously with water.

**SECTION 5 : FIREFIGHTING MEASURES**

Non-flammable.

**5.1. Extinguishing media**

No data available.

**5.2. Special hazards arising from the substance or mixture**

No data available.

**5.3. Advice for firefighters**

No data available.

**SECTION 6 : ACCIDENTAL RELEASE MEASURES****6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Avoid contact with eyes and skin and breathing dust. Use the product with suitable working clothes (goggles, working-suit, boots,...) and wear a dust mask in case of dust in air.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Use drums to dispose of waste recovered in accordance with applicable regulations (see heading 13).

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Avoid spilling of powder in large quantities into sewers and waterways.

**6.3. Methods and material for containment and cleaning up**

Collect product by machine and transfer to suitable container.

After setting, the product can be disposed of as an usual construction waste.

**6.4. Reference to other sections**

No data available.

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

The product should be handled in well-ventilated areas. Avoid the creation of dust. In case of airborne dust, use a powder mask.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling dust.

Avoid eye contact with this mixture at all times.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep out of reach of children.

In dry conditions.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters****Occupational exposure limits :**

- European Union (2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m <sup>3</sup> :	VME-ppm :	VLE-mg/m <sup>3</sup> :	VLE-ppm :	Notes :
1305-62-0	1	-	4	-	-

- Germany - AGW (BAuA - TRGS 900, 29/01/2018) :

CAS	VME :	VME :	Excess	Notes
65997-15-1	-	5 mg/m <sup>3</sup> E	-	DFG
1305-62-0		1 E mg/m <sup>3</sup>		2(I)

- Belgium (Arrêté du 09/03/2014, 2014) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
14808-60-7	0,1 mg/m <sup>3</sup>				
471-34-1	10 mg/m <sup>3</sup>	-	-	-	-
65997-15-1	10 mg/m <sup>3</sup>				
1317-65-3	10 mg/m <sup>3</sup>				
1305-62-0	5 mg/m <sup>3</sup>				

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m <sup>3</sup> :	VLE-ppm :	VLE-mg/m <sup>3</sup> :	Notes :	TMP No :
14808-60-7	-	0.1 A	-	-	-	25
471-34-1	-	10	-	-	-	-
1317-65-3	-	10	-	-	-	-
1305-62-0	-	5	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
14808-60-7	0.3 mg/m <sup>3</sup>	-	-	-	R
471-34-1	10 mg/m <sup>3</sup>	-	-	-	TI
65997-15-1	- ppm 4 mg/m <sup>3</sup>	- ppm - mg/m <sup>3</sup>			
1317-65-3	- ppm 4 mg/m <sup>3</sup>	- ppm - mg/m <sup>3</sup>			
1305-62-0	- ppm 5 mg/m <sup>3</sup>	- ppm - mg/m <sup>3</sup>			

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

CALCIUM DIHYDROXIDE (CAS: 1305-62-0)

<b>Final use:</b>	<b>Workers.</b>
Exposure method:	Inhalation.
Potential health effects:	Short term local effects.
DNEL :	4 mg of substance/m3

Exposure method:	Inhalation.
Potential health effects:	Long term local effects.
DNEL :	1 mg of substance/m3

<b>Final use:</b>	<b>Consumers.</b>
Exposure method:	Inhalation.
Potential health effects:	Short term local effects.
DNEL :	4 mg of substance/m3

Exposure method:	Inhalation.
Potential health effects:	Long term local effects.
DNEL :	1 mg of substance/m3

PORTLAND CEMENT CLINKER (CAS: 65997-15-1)

<b>Final use:</b>	<b>Workers.</b>
Exposure method:	Inhalation.
Potential health effects:	Short term local effects.
DNEL :	3 mg of substance/m3

CALCIUM CARBONATE (CAS: 471-34-1)

<b>Final use:</b>	<b>Workers.</b>
Exposure method:	Inhalation.
Potential health effects:	Long term local effects.
DNEL :	4.26 mg of substance/m3

Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	10 mg of substance/m3

<b>Final use:</b>	<b>Consumers.</b>
Exposure method:	Inhalation.
Potential health effects:	Long term local effects.
DNEL :	1.06 mg of substance/m3

Exposure method:	Inhalation.
Potential health effects:	Long term systemic effects.
DNEL :	10 mg of substance/m3

**Predicted no effect concentration (PNEC):**

CALCIUM DIHYDROXIDE (CAS: 1305-62-0)

Environmental compartment:	Soil.
PNEC :	1080 mg/kg

Environmental compartment:	Fresh water.
PNEC :	0.49 mg/l

Environmental compartment:	Sea water.
PNEC :	0.32 mg/l

Environmental compartment:	Waste water treatment plant.
PNEC :	3 mg/l

CALCIUM CARBONATE (CAS: 471-34-1)

Environmental compartment:	Waste water treatment plant.
PNEC :	100 mg/l

**8.2. Exposure controls****Appropriate engineering controls**

Avoid contact with mucous membranes, eyes and hands.  
Do not rub the eyes with dirty hands.  
Anyone with a history of skin sensitisation must on no account handle such products.

**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.  
Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.  
Before handling powders or dust emission, wear mask goggles in accordance with standard EN166.  
Prescription glasses are not considered as protection.  
Envisage in the vicinity a clean water container or an ocular fountain in the event of projection in the eyes  
In case of powder or paste splashing risk, use protective glasses goggles.

**- Hand protection**

Wear suitable protective gloves in the event of prolonged or repeated skin contact.  
Waterproof work gloves or creams.  
Waterproof neoprene or nitrile protective gloves lined with cotton or jersey (in accordance with EN 374).

**- Body protection**

Avoid skin contact.  
Work clothing worn by personnel shall be laundered regularly.  
After contact with the product, all parts of the body that have been soiled must be washed.  
Closed working clothes protecting forearms in continuous with gloves. In case of kneeling work, waterproof kneepads are recommended.  
Protective "barrier" creams can be used. Avoid prolonged contact. Ensure that no product remains between the skin and the clothes, the watch, the shoes.

**- Respiratory protection**

Avoid breathing dust.  
Type of FFP mask :  
Wear a disposable half-mask dust filter in accordance with standard EN149.  
Category :  
- FFP2  
Powder mask in case of airborne dust.

**- Thermal risks**

The substance shows no thermal hazard.

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties****General information :**

Physical state :	Powder or dust.
------------------	-----------------

**Important health, safety and environmental information**

pH :	Not stated. Strongly basic.
Boiling point/boiling range :	Not relevant.
Flash point interval :	Not relevant.
Vapour pressure (50°C) :	Not relevant.
Density :	> 1
Water solubility :	Dilutable.
Melting point/melting range :	Not relevant.
Self-ignition temperature :	Not relevant.
Decomposition point/decomposition range :	Not relevant.

**9.2. Other information**

No data available.

**SECTION 10 : STABILITY AND REACTIVITY****10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

Avoid :

- humidity

The mortar can harden in humid conditions.

**10.5. Incompatible materials**

No data available.

**10.6. Hazardous decomposition products**

No data available.

**SECTION 11 : TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

May cause an allergic reaction by skin contact.

**11.1.1. Substances****Acute toxicity :**

PORTLAND CEMENT CLINKER (CAS: 65997-15-1)

Dermal route : LD50 > 2000 mg/kg  
Species : Rabbit

CALCIUM DIHYDROXIDE (CAS: 1305-62-0)

Oral route : LD50 > 2000 mg/kg  
Species : Rat  
OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

Dermal route : LD50 > 2500 mg/kg  
Species : Rabbit  
OECD Guideline 402 (Acute Dermal Toxicity)

HYDRAULIC LIME (CAS: 85117-09-5)

Oral route : LD50 > 2000 mg/kg  
Species : Rat  
OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

NATURAL CALCIUM CARBONATE (CAS: 1317-65-3)

Oral route : LD50 > 5000 mg/kg  
Species : Rat

CALCIUM CARBONATE (CAS: 471-34-1)

Oral route : LD50 > 2000 mg/kg  
Species : Rat  
OECD Guideline 420 (Acute Oral Toxicity Fixed Dose Method)

Dermal route : LD50 > 2000 mg/kg  
Species : Rat  
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (Dusts/mist) : LC50 > 3 mg/l

Species : Rat  
OECD Guideline 403 (Acute Inhalation Toxicity)

QUARTZ (CAS: 14808-60-7)

Oral route : LD50 > 2000 mg/kg

Dermal route : LD50 > 2000 mg/kg

**Skin corrosion/skin irritation :**

CALCIUM DIHYDROXIDE (CAS: 1305-62-0)

Irritation :

Effect observed : Overall irritation score  
Causes skin irritation.  
2.3 <= Average score <= 4.0  
Species : Rabbit  
OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

CALCIUM CARBONATE (CAS: 471-34-1)

Species : Rabbit  
OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Species : Rabbit  
OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious damage to eyes/eye irritation :**

CALCIUM DIHYDROXIDE (CAS: 1305-62-0)

Causes serious eye damage.

Corneal haze : Average score >= 3  
Species : Rabbit

Iritis : Average score > 1.5  
Species : Rabbit

The substance produces at least in one animal effects on the conjunctiva that are not expected to reverse or have not fully reversed within an observation period of normally 21 days.

Species : Rabbit

Species : Guinea pig

PORTLAND CEMENT CLINKER (CAS: 65997-15-1)

Corneal haze : Average score = 128

CALCIUM CARBONATE (CAS: 471-34-1)

Species : Rabbit  
OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Species : Rabbit  
OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Species : Rabbit  
OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Species : Rabbit  
OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitisation :**

CALCIUM CARBONATE (CAS: 471-34-1)

Local lymph node stimulation test : Non-Sensitiser.  
Species : Mouse  
OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Guinea Pig Maximisation Test (GMPT) : Non-sensitiser.



Species : Mouse  
OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Buehler Test :

Non-sensitiser.  
Species : Mouse  
OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

#### Germ cell mutagenicity :

CALCIUM DIHYDROXIDE (CAS: 1305-62-0)  
Mutagenesis (in vitro) :

Negative.  
Species : Mammalian Cell Line  
OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Ames test (in vitro) :

Negative.

HYDRAULIC LIME (CAS: 85117-09-5)  
Mutagenesis (in vitro) :

Negative.  
Species : Mammalian Cell Line  
OECD Guideline 471 (Bacterial Reverse Mutation Assay)

CALCIUM CARBONATE (CAS: 471-34-1)

No mutagenic effect.

Mutagenesis (in vitro) :

Negative.  
OECD Guideline 471 (Bacterial Reverse Mutation Assay)

#### Carcinogenicity :

CALCIUM CARBONATE (CAS: 471-34-1)  
Carcinogenicity Test :

Negative.  
No carcinogenic effect.  
Species : Human

#### Reproductive toxicant :

CALCIUM CARBONATE (CAS: 471-34-1)  
No toxic effect for reproduction  
Study on development :

Species : Rat  
OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

#### Specific target organ systemic toxicity - repeated exposure :

CALCIUM DIHYDROXIDE (CAS: 1305-62-0)  
Oral route :

C = 36 mg/kg bodyweight/day  
Duration of exposure : 90 days

CALCIUM CARBONATE (CAS: 471-34-1)  
Oral route :

C = 1000 mg/kg bodyweight/day  
Species : Rat  
OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Inhalation route :

C = 0.212 mg/litre/6h/day  
Species : Rat  
OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

#### 11.1.2. Mixture

##### Skin corrosion/skin irritation :

In case of damp skin, the partial hydration of cement increases the pH and can irritate the skin. A prolonged contact with a cement paste can induce skin burning.

##### Serious damage to eyes/eye irritation :

The cement can induce eyelids irritation (blepharitis), corneal irritation (conjunctivitis) and create eyeball injury.

##### Respiratory or skin sensitisation :

The cement can induce irritation of the respiratory tract and a nasal mucous inflammation. In extreme case, mucous erosion has been observed.

Prolonged exposure without proper protection (gloves) can cause skin irritation (fissural dermatitis). In subjects prone to allergies, these lesions may precede an allergy to certain elements present in trace amounts in the cement. Other lesions may be encountered with unprotected prolonged contact. They usually appear on fingers fissural dermatitis, ulcers, kyperkératoses.  
May cause an allergic skin reaction.

**Other information**

If significant swallowed, cement is caustic for the digestive tract, it may cause burns of the mouth, oesophagus and stomach.

**SECTION 12 : ECOLOGICAL INFORMATION****12.1. Toxicity****12.1.1. Substances**

CALCIUM CARBONATE (CAS: 471-34-1)

Algae toxicity :

NOEC > 14 mg/l

Species : *Desmodesmus subspicatus*

Duration of exposure : 72 h

OECD Guideline 201 (Alga, Growth Inhibition Test)

CALCIUM DIHYDROXIDE (CAS: 1305-62-0)

Fish toxicity :

LC50 = 50.6 mg/l

Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 49.1 mg/l

Duration of exposure : 48 h

NOEC = 32 mg/l

Species : *Daphnia magna*

Duration of exposure : 14 days

Algae toxicity :

ECr50 = 184.57 mg/l

Duration of exposure : 72 h

NOEC = 48 mg/l

Duration of exposure : 72 h

HYDRAULIC LIME (CAS: 85117-09-5)

Fish toxicity :

LC50 = 50.6 mg/l

Duration of exposure : 96 h

Crustacean toxicity :

EC50 = 49.1 mg/l

Duration of exposure : 48 h

NOEC = 32 mg/l

Duration of exposure : 14 days

Algae toxicity :

ECr50 = 184.57 mg/l

Duration of exposure : 72 h

NOEC = 48 mg/l

Duration of exposure : 72 h

NATURAL CALCIUM CARBONATE (CAS: 1317-65-3)

Fish toxicity :

LC50 > 10000 mg/l

Species : *Oncorhynchus mykiss*

Duration of exposure : 96 h

Crustacean toxicity :

EC50 > 1000 mg/l

Species : *Daphnia magna*

Duration of exposure : 48 h

Algae toxicity :

ECr50 > 200 mg/l

Species : *Desmodesmus subspicatus*

Duration of exposure : 72 h

#### 12.1.2. Mixtures

The product must not be allowed to run into drains or waterways.

#### 12.2. Persistence and degradability

##### 12.2.1. Substances

HYDRAULIC LIME (CAS: 85117-09-5)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

#### 12.3. Bioaccumulative potential

none.

#### 12.4. Mobility in soil

none.

#### 12.5. Results of PBT and vPvB assessment

No data available.

#### 12.6. Other adverse effects

In case of accidental pouring in waste water, the product causes a low pH rise . Cement is a stable material that permanently fixes its compounds and makes them insoluble.

### SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

#### 13.1. Waste treatment methods

Do not pour into drains or waterways.

After curing, the mortar can be removed like other construction debris and stored in landfills in accordance with appropriate regulations.

##### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

##### Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

##### Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

17 01 01 concrete

### SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

#### 14.1. UN number

-

#### 14.2. UN proper shipping name

-

#### 14.3. Transport hazard class(es)

-

#### 14.4. Packing group

-

#### 14.5. Environmental hazards

-

#### 14.6. Special precautions for user

-

### SECTION 15 : REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)

##### - Container information:


No data available.

**- Particular provisions :**

No data available.

**- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :**

NFPA 704, Labelling: Health=3 Inflammability=1 Instability/Reactivity=1 Specific Risk=none

**15.2. Chemical safety assessment**

No data available.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

**Abbreviations :**

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

GHS05 : Corrosion

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.